## IN THE CLAIMS

Please add a page break, after the paragraph on page 13, lines 14-21.

Please change the heading on page 13 before the claims as follows:

## CLAIMS<del>Patent claims:</del>

## What is claimed is:

1. (Currently amended) A pProcess for the packetoriented transmission of security-relevant data (11, 11b, 12, 12b), in particular under application of at least one transmission system with comprising a parallel and/or serial network and/or bus system with at least one user connected to it, the process, comprising:

redundant information based on the security-relevant

data, where in addition to the security-relevant data (11, 11b, 12, 12b) a redundant information based on the data

(21, 21b) is transmitted,

wherein characterized in that the security-relevant data (11, 11b, 12, 12b) and the redundant information based on this data (21, 21b) areis transmitted in different packets (1, 1b, 2, 2b).

- 2. (Currently amended) The process according to celaim 1, whereineharacterized in that the redundant information (21, 21b) is encoded.
- 3. (Currently amended) The process according to celaim 1, whereiner 2 characterized in that the redundant

information  $\frac{(21, 21b)}{}$  is a check sum (CRC) calculated over the security-relevant data.

- 4. (Currently amended) The process according to celaim 1, wherein, 2 or 3 characterized in that the security-relevant data is selected from the group consisting of comprise user data (11, 11b), check data, (12, 12b) and/or control data.
- 5. (Currently amended) The process according to claim 1, further comprising transmitting one of the Claims 1 through 4 characterized in that several packets (1, 1b, 2, 2b) are transmitted within a predefined (superset) frame structure.
- 6. (Currently amended) The pProcess according to claim 5, whereinone of the Claims 1 through 5 characterized in that the packets within a predefined (superset) frame structure) includecomprise the security-relevant data (11, 11b, 12, 12b) and the redundant information (21, 21b)—that are allocated to each other.
- 7. (Currently amended) The pProcess according to claim 6, whereinone of the Claims 1 through 6 characterized in that the packets (1, 1b, 2, 2b) with the security-relevant data (11, 11b, 12, 12b) and the redundant information (21, 21b) that are allocated to each other are transmitted in a parallel or serial way.
- 8. (Currently amended) The pProcess according to claim 6, wherein one of the Claims 1 through 7 characterized in that the packets (1, 1b, 2, 2b) with the security-relevant data and the redundant information that are allocated to each other are transmitted in strings or

separately.

- 9. (Currently amended) The process according to claim 1, whereinone of the Claims 1 through 8 characterized in that the packets include(1, 1b, 2, 2b) comprise an addressing block and/or an identification code for their logical allocation.
- 10. (Currently amended) A device, in particular for a transmission system with at least one parallel and/or serial network and/or bus system, for the packet-oriented transmission of security-relevant data (11, 11b, 12, 12b), comprising:

means,—arranged on the side of the sender,— for the packet-oriented embedding of the security-relevant data (11, 11b, 12, 12b)—and the allocated redundant information (21, 21b)—into different packets—(1, 1b, 2, 2b).

- 11. (Currently amended) The device according to celaim 10, further comprising characterized by an encoding device for the encoding of the redundant information (21, 21b).
- 12. (Currently amended) The derived according to celaim 10 whereiner 11 characterized in that the means for embedding are allocated means for the generation of the redundant information (21, 21b) with the same number of bits (n) as the security-relevant data (11, 11b, 12, 12b) to be transmitted.
- 13. (Currently amended) The device according to celaim 10 wherein, 11 or 12 characterized in that the means for the generation and/or embedding are designed such that any possible combination of the security-oriented data

- $\frac{(11, 11b, 12, 12b)}{(11, 11b, 12, 12b)}$  of a packet  $\frac{(1, 1b)}{(11, 1b)}$  unambiguously results in exactly one of the possible combinations with the allocated redundant information  $\frac{(21, 21b)}{(2, 2b)}$ .
- 14. (Currently amended) The dDevice, in particular for a transmission system with at least one parallel and/or serial network and/or bus system, for the packet-oriented transmission of security-relevant data (11, 11b, 12, 12b), in particular according to claim 10, further comprisingone of the Claims 10 through 13 characterized by means arranged on the side of the receiver for the verification of an error-free data transmission based on the security-relevant data (11, 11b, 12, 12b) and the allocated redundant information (21, 21b) embedded in different packets—(1, 1b, 2, 2b).
- 15. (Currently amended) The derice according to celaim 14 whereineharacterized in that the means for the verification are allocated means for reading out and allocating security-relevant data (11, 11b, 12, 12b) and allocated redundant information (21, 21b) received in different packets.
- 16. (Currently amended) The derice according to claim 10, whereinone of the Claims 10 through 15 characterized in that several packets (1, 1b, 2, 2b) with the security-relevant data (11, 11b, 12, 12b) and/or the allocated redundant information are capable of being (21, 21b) can be transmitted within a predefined (superset) frame structure.
- 17. (Currently amended) <u>The dDevice according to claim</u>
  10, further comprising one of the Claims 10 through 16

characterized by means for the packet-oriented embedding and readout of addressing blocks and/or identification codes for the logical allocation of individual packets (1, 1b, 2, 2b) and/or their contents (11, 11b, 12, 12b, 21, 21b) to each other.

- 18. (Currently amended) The device according to claim 10, whereinone of the Claims 10 through 17 characterized in that the means are allocated to slave devices and/or a master device.
- 19. (Currently amended) <u>A t</u>Transmission system comprising: with

at least one parallel and/or serial —network and/or bus system; and with

at least one device according to claim  $10 \frac{\text{one of the}}{\text{claims } 10 \text{ through } 18}$ .

- 20. (Currently amended) The tTransmission system according to cClaim 19, wherein the network and/or bus system there is at least one ring-, line-, star- and/or tree-shaped network and/or bus structure.
- 21. (Currently amended) The tTransmission system according to cElaim 19, wherein the network and/or bus system isor 20 comprising at least one selected from the group consisting of Interbus, one Ethernet, one Profibus, and/or one CAN.
- 22. (Currently amended) Use of a transmission system according to <a href="mailto:claim 19Claim 19">claim 19</a>, 20 or 21 in <a href="mailto:athe-field-selected from the group consisting">athe field-selected from the group consisting</a> of building control technology, process industry, manufacturing industry,

passenger transportation, and  $\frac{1}{\sqrt{1 - 1}}$  operation of an automation plant.